

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

THIS PAGE BLANK (USPTO)



GAU 3652

06007/37458
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of:

DAVID ALLAN COOK, ET AL.

Serial No.: 09/866,311

Filed: May 25, 2001


For: HYDRAULIC SYSTEM FOR
WHEELED LOADER

Group Art Unit: 3652

Examiner: Unknown

CERTIFICATE OF MAILING

I hereby certify that this
paper and the documents
referred to as enclosed
therewith are being deposited
with the United States Postal
Service as first class mail,
postage prepaid, on August 28,
2001 in an envelope addressed
to Commissioner for Patents,
Washington, D.C. 20231:


Nate F. Scarpelli

#1
PRIORITY
PAPER
ASW
9-20-01

TRANSMITTAL OF PRIORITY DOCUMENTCommissioner for Patents
Washington, D.C. 20231

Sir:

Enclosed herewith is a certified copy of Great
Britain Patent Application No. 0012602.9, filed May 25, 2000,
upon which priority of the instant application is claimed
under 35 U.S.C. §119.


Respectfully submitted,
MARSHALL, GERSTEIN & BORUN
6300 Sears Tower
233 South Wacker Drive
Chicago, Illinois 60606-6402
Tel.: (312) 474-6300
Fax (312) 474-0448

RECEIVED

SEP 04 2001

173600 MAIL ROOMS

By:


Nate F. Scarpelli
Reg. No. 22,320

August 28, 2001

THIS PAGE BLANK (USPTO)



09/866,311
Group 3652
06007/37458
INVESTOR IN PEOPLE
The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed




Dated 13 June 2001

THIS PAGE BLANK (USPTO)

Request for grant of a patent

25 MAY 2000



The Patent Office

Cardiff Road
Newport
South Wales NP10 8QQ

1. Your reference **A9996GB-JNL**

2. Patent application number **0012602.9**
(The Patent Office will fill in this part)

25MAY00 E539607-3 D02811
P01/7700 0.00-0012602.9

3. Full name, address and postcode of the or of each applicant (underline all surnames)

J.C.Bamford Excavators Limited
Rocester
Uttoxeter
Staffordshire ST14 5JP

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

528281002
UNITED KINGDOM

4. Title of the invention

Hydraulic System for Wheeled Loader

5. Name of your agent (if you have one)

Forrester Ketley & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Chamberlain House
Paradise Place
Birmingham, B3 3HP.

Patents ADP number (if you know it)

133005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:

YES

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form -

Description 7

Claim(s) 2

Abstract 1

Drawing(s) 6 X 6

10. If you are also filing any of the following, state how many against each item.

Priority documents NONE

Translation of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents -
(please specify)

11. I/We request the grant of a patent based on the basis of this application

Signature

Forrester Ketley & Co.

Date

24 May, 2000

Forrester Ketley & Co.

12. Name and daytime telephone number of person to contact in the United Kingdom

J N Leach

0121 236 0484

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) if you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered "Yes" Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

PATENTS ACT 1977

A9996GB-JNL

Title: Hydraulic System for Wheeled Loader

Description of Invention

This invention relates to a hydraulic system for a wheeled loader having a loader arm assembly which carries a working implement and in which the loader arm assembly is connected to the body and which is movable between raised and lowered positions by means of a hydraulic ram means.

It is known to improve the ride of such a wheeled loader by connecting an hydraulic accumulator into the hydraulic hose which feeds hydraulic fluid into said ram means to raise the loader arm assembly. As a result when the wheeled loader is travelling across a site, or when travelling along a road, at speed the loader arm assembly is suspended in spring manner by the accumulator and so the wheeled loader is able to travel with less pitch and bounce than would otherwise have been the case.

However, such a ride improvement system has not been provided hitherto in a loader vehicle comprising a loader arm assembly connected at, or adjacent to, the rear end of the assembly to the body at, or adjacent to, the rear end of the body so that the loader arm assembly extends forwardly whereby, in a lowered position of the arm assembly, the working implement is disposed in front of the body. Such a vehicle is provided with a hose burst check valve.

According to the present we provide an hydraulic system for a wheeled loader having a loader arm assembly which carries a working implement and which is connected to the body and which is movable between raised and lowered positions by means of a hydraulic ram means and in which a hydraulic accumulator is connected to the hydraulic ram means wherein the loader arm assembly is connected at, or adjacent to, the rear end thereof to the body at, or adjacent to, the rear end thereof so that the loader arm assembly extends forwardly whereby, in a lowered position of the loader arm assembly, the

working implement is disposed in front of the body wherein each chamber of the hydraulic ram means is connected to a selection valve means adapted to feed fluid under pressure to one chamber of the ram means and to receive fluid at a lower pressure from the other chamber of the ram means in order to raise the loader arm assembly or to feed fluid under pressure to said other chamber of the ram means and receive fluid at a lower pressure from said one chamber of the ram means to lower the loader arm assembly, first and second control valves each of which is movable between a first position in which passage of hydraulic fluid therethrough is prevented in one or both directions respectively to a second position in which passage of hydraulic fluid therethrough is permitted, said first control valve means being connected between said first chamber and said accumulator and said second control valve means being connected between said second chamber and a low pressure region and there being a check valve connected between the first chamber and the selection valve means such that the check valve is normally closed to prevent fluid under pressure passing from said first chamber to the selection valve means and having hydraulic fluid responsive means to open said check valve and there being means to connect said hydraulic fluid pressure means to said second chamber so as to open the check valve.

The selection valve may be manually operable.

The control valves may be electrically operated solenoid valves to which current is supplied by a manually operable switch means to cause operation of said ride improvement means when said valves are positioned to permit passage of hydraulic fluid.

The selection valve may be provided with a switch means to sense the position of the selection valve to close said second control valve when the boom is lowered and said control valves are open.

The accumulator and the control valves and the check valves may be mounted directly on the ram.

At least one of said accumulator, solenoid valves, check valves and connecting pipework may be made in metal, preferably steel.

Said check valve may be a hose burst check valve.

Said one chamber may be disposed on the opposite side of the valve to the piston rod and said other chamber may be an annular chamber surrounding said piston rod.

An example of the invention will now be described with reference to the accompanying drawings wherein:

Figure 1 is a side view of a vehicle according to the invention,

Figure 2 is a diagrammatic circuit diagram showing the flow of hydraulic fluid and valve positions in normal operation of the vehicle during lifting of the arm,

Figure 3 is a view similar to that of Figure 2 but showing normal operation during lowering of the arm,

Figure 4 is a view similar to that of Figure 2 but showing a travel position of the vehicle with the ride improvement means engaged,

Figure 5 is a view similar to that of Figure 4 but showing a boom lift position and ride improvement means engaged.

Figure 6 is a view similar to that of Figure 4 but showing flow of fluid in a boom lower position with the ride improvement means engaged.

Referring to the drawings, a wheeled loader vehicle comprises a body 10 supported, in conventional manner, on two pairs of front and rear wheels 11, 12 each of which is steerable and each of which is driven by a suitable transmission and differential means from an engine which may be disposed as desired on the vehicle. The body 10 has a rear end 13 and a front end 14. A loader arm assembly 16, at a position adjacent its rear end, is pivotally mounted to the body 10 adjacent the rear end 13 of the body, about an axis 15. The loader arm assembly 16 in the present example, is a two part boom having an outer part 16a, within which is telescoped an inner part 16b and which parts are

slidable relative to each other by hydraulic ram means so as to provide an extendible loader arm assembly. If desired the vehicle may have a two or more part boom or an un-extendible single part boom.

At the front end of the boom assembly 16 is a downwardly extending nose part 17 by which a working implement 18 is releasably carried in conventional manner. If desired, the working implement 18 may be a pair of lifting tines as shown or may be a bucket or any other suitable working implement.

The loader arm assembly may be connected to the body at or adjacent the rear thereof, by any suitable pivot means disposed at or adjacent the rear of the loader arm assembly.

The loader arm assembly 16 is pivotable about the axis 15 between raised and lowered positions. In the lowered position working implement 18 is disposed in front of the vehicle front end 14. The loader arm assembly 16 is movable between said raised and lowered positions by a ram assembly 20, which in the present example comprises a single ram. The ram assembly 20, in conventional manner, comprises a cylinder part 21 and a piston rod 22. The piston rod 22 is connected at one end to a bracket 23 depending downwardly from the underside of the part 16a of the lowered arm assembly by means of a pivot pin 24a whilst the cylinder 21 is connected, at its lower end, by a pivot pin 24b to a part of the body 10. Obviously extension and retraction of the piston rod 22 from the cylinder 21 causes pivotal raising and lowering of the arm assembly 16.

Within the cylinder 21 is a first chamber 25, on one side of the piston 27, which is of cylindrical configuration and a second chamber 26 on the opposite side of the piston 27, see Figures 2 to 5, to the first chamber 25 and which is of annular configuration in cross section. Mounted on the cylinder 21 is a conventional accumulator means 30 made of, in the present example, steel and connected by a pipe 31 to a first control valve 32. A second control valve

33 is connected by a line 34 comprising flexible hoses and/or rigid pipes to an hydraulic reservoir or other low pressure area 35.

Each control valve 32, 33 is an electrically operated solenoid valve and which is movable between a first or "at rest" position in which passage of fluid is prevented in one direction of the valve 32 and in both directions in the valve 33 and a second position in which passage of fluid is permitted. Both control valves 32, 33 are normally spring biased by a spring means 36 to the position in which flow of fluid is prevented as illustrated in Figure 2 and Figure 3.

A line 38, comprising a rigid pipe 38a and a flexible line 38b, connects the first chamber 25 of the ram 20 to a first port 40a of a selection valve 40 via a hose burst check valve 39. The first control valve 32 is connected by a line 37, comprising a rigid pipe, to the line 38 between ram chamber 25 and the hose burst check valve 39. The hose burst check valve 39 is a pilot valve that is normally maintained closed in the direction to prevent flow of fluid under pressure from the chamber 25 to the valve 40 but it may be opened by supply of pilot pressure on line 41, comprising a rigid pipe, from a line 42, comprising a rigid pipe 42a and flexible hoses 42b which extends between a second port 40b of the selection valve 40 and the chamber 26 of the ram 20. The line 42 is connected by a line 43 to the second control valve 33.

In use, as best shown in Figure 2, during normal operation, when it is desired to lift the arm, fluid under pressure is fed from the first port 40a of the selection valve 40 along the line 38 through the one-way check valve within the hose burst check valve 39. As boom suspension has not been selected there is no electrical supply to valves 32 and 33 and they remain in the normally closed position. As the telescopic boom 16 is raised, by the supply of fluid to the chamber 25, fluid under lower pressure is fed from the chamber 26 along line 42 into a port 40b of the selection valve 40. The valve 33, of course, being, like the valve 32, maintained in the position shown in Figure 2 to prevent flow

of fluid therethrough by virtue of no electrical supply being supplied to the solenoid thereof.

Referring now to Figure 3, when it is desired to lower the loader arm assembly the valve 40 is actuated to feed fluid under pressure through port 40b along line 42 into the chamber 26 and thus fluid under lower pressure is fed from chamber 25 along line 38 through hose burst check valve 39 which is maintained in an open position by virtue of supply of pilot pressure on line 41 which extends from line 42.

Referring now to Figure 4, when it is desired to operate the ride improvement means i.e. boom suspension means the system is activated by operation of a suitable electric control so that electrical supply is provided to the valves 32, 33 to move them from the positions shown Figures 2 and 3 to the positions shown in Figures 4 to 6 in which passage of hydraulic fluid is permitted.

In this position fluid can flow both to the accumulator 30 and also to the reservoir 35 in accordance with the external forces imposed on the piston 27 to displace fluid to or from chambers 25, 26. Such a condition is shown in Figure 4. As a result the loader arm is supported by the action of the accumulator on the hydraulic fluid and it is, in effect, sprung.

Referring now to Figure 5, when it is desired to raise the loader arm assembly whilst the ride improvement means is engaged, the valve 40 is actuated to feed fluid from port 40a under pressure along line 38 into the chamber 25 whilst fluid from the chamber 26 passes along the line 42 back to the valve 40. At the same time the suspension of the arm assembly is suspended by the accumulator 30 as described hereinbefore in connection with the Figure 4.

Referring now to Figure 6, when it is desired to lower the boom whilst the ride improvement means is engaged, the actuation of the valve 40 to raise pressure at port 40b, by virtue of switch 44, has the effect of collapsing the

electrical signal to valve 33 which becomes closed and so allows pressure to be raised in line 42 which feeds fluid under pressure to chamber 26, whilst fluid in chamber 25 is fed via line 38 through the hose burst check valve 39 to the port 40a of the valve 40. The hose burst check valve 39 is maintained open by pilot pressure fluid on line 41 which extends from line 42.

Whilst in this example the accumulator 30, valves 32, 33 and check valve 39 are all disposed on the cylinder 21, if desired one or more of these components may be positioned as desired and made of material as desired where permitted by local regulations.

In the present specification "comprise" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. An hydraulic system for a wheeled loader having a loader arm assembly which carries a working implement and which is connected to the body and which is movable between raised and lowered positions by means of a hydraulic ram means and in which a hydraulic accumulator is connected to the hydraulic ram means wherein the loader arm assembly is connected at, or adjacent to, the rear end thereof to the body at, or adjacent to, the rear end thereof so that the loader arm assembly extends forwardly whereby, in a lowered position of the loader arm assembly, the working implement is disposed in front of the body wherein each chamber of the hydraulic ram means is connected to a selection valve means adapted to feed fluid under pressure to one chamber of the ram means and to receive fluid at a lower pressure from the other chamber of the ram means in order to raise the loader arm assembly or to feed fluid under pressure to said other chamber of the ram means and receive fluid at a lower pressure from said one chamber of the ram means to lower the loader arm assembly, first and second control valves each of which is movable between a first position in which passage of hydraulic fluid therethrough is prevented in one or both directions respectively to a second position in which passage of hydraulic fluid therethrough is permitted, said first control valve means being connected between said first chamber and said accumulator and said second valve means being connected between said second chamber and a low pressure region and there being a check valve connected between the first chamber and the selection valve means such that the check valve is normally closed to prevent fluid under pressure passing from said first chamber to the selection valve means and having hydraulic fluid responsive means to open said check valve and there being means to connect said hydraulic fluid pressure means to said second chamber so as to open the check valve.

2. A system according to Claim 1 wherein the selection valve is manually operable.
3. A system according to any one of the preceding claims wherein the control valves are electrically operated solenoid valves to which current is supplied by a manually operable switch means to cause operation of said ride improvement means when said valves are positioned to permit passage of hydraulic fluid.
4. A system according to Claim 4 or Claim 3 wherein the selection valve is provided with a switch means to sense the position of the selection valve to close said second control valve when the boom is lowered and said control valves are open.
5. A system according to any one of the preceding claims wherein the accumulator and the control valves and the check valve are mounted directly on the ram.
6. A system according to any one of the preceding claims wherein at least one of said accumulator, solenoid valves and check valves and connecting pipes are made in metal.
7. An hydraulic system substantially as hereinbefore described with reference to the accompanying drawings.
8. Any novel feature or novel combination of features described herein and/or in the accompanying drawings.

ABSTRACT

Title: Hydraulic System for Wheeled Loader

An hydraulic system for a wheeled loader comprising a loader arm assembly which carries a working implement and which is connected to the body and which is movable between raised and lowered positions by means of a hydraulic ram means and in which a hydraulic accumulator is connected to the hydraulic ram means wherein the loader arm assembly is connected at, or adjacent to, the rear end thereof to the body at, or adjacent to, the rear end thereof so that the loader arm assembly extends forwardly whereby, in a lowered position of the loader arm assembly, the working implement is disposed in front of the body wherein each chamber of the hydraulic ram means is connected to a selection valve means adapted to feed fluid under pressure to one chamber of the ram means and to receive fluid at a lower pressure from the other chamber of the ram means in order to raise the loader arm assembly or to feed fluid under pressure to said other chamber of the ram means and receive fluid at a lower pressure from said one chamber of the ram means to lower the loader arm assembly, first and second control valves each of which is movable between a first position in which passage of hydraulic fluid therethrough is prevented in one or both directions respectively to a second position in which passage of hydraulic fluid therethrough is permitted, said first control valve means being connected between said first chamber and said accumulator and said second valve means being connected between said second chamber and a low pressure region and there being a check valve connected between the first chamber and the selection valve means such that the check valve is normally closed to prevent fluid under pressure passing from said first chamber to the selection valve means and having hydraulic fluid responsive means to open said check valve and there being means to connect said hydraulic fluid pressure means to said second chamber so as to open the check valve.

1 / 6





FIG 1

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)

A thick vertical black line runs along the right edge of the page, starting from the bottom and extending upwards.




FIG. 3

THIS PAGE BLANK (USPTO)




FIG 4

THIS PAGE BLANK (USPTO)




FIG 5

THIS PAGE BLANK (USPTO)




FIG 6

THIS PAGE BLANK (USPTO)